

Entrance matting technical data sheet

Issue number 18.1 to check if you have our latest sheet visit tier-global.com/download

Technical data sheet specification

Fibre type	100% Polypropylene
Product construction	Fibrebonded
Pile height	10.5 mm
Backing type sheet	Synthetic rubber
Backing type tile	Bitumen (12 tiles per box)
Fibre weight	1500 g/m ²
Total weight	2650 g/m ²
Roll size	2 x 12.5m
Colourways	8
Wear grade	Heavy contract

Installation

All products should be installed to CFA guidelines and BS5325 'Code of practice for the Installation of Textile Floor Coverings.'

Lay on a smooth, clean, dry and damp-proof subfloor, and to the adhesive manufacturer's instruction.

Carpet in the same room/area must be from the same dye batch (given on the label of the box).

Observe a consistent pile direction. Tier Global suggests that linear effect designs should be fitted in a quarter turn pattern.

Maintenance

Vacuum daily using a commercial upright vacuum cleaner with a driven brush which contacts the pile. Treat spots and spillages immediately. Deep cleaning periodically and use will castor chair mats.

Please note: It is not possible to colour match from different dye batches and blends of yarn. Areas which need to colour match should be ordered and fitted at the same time. Please allow for possible variation in supplied material to the shade card samples.

Tier Global (UK) Limited reserves the right to modify the content of technical data sheets without prior notice.

5 year warranty

Tier entrance matting carpet tile supplied by Tier Global (UK) Limited is fully warranted as follows:

1. The carpet tile is fully warranted against raw material and manufacturing defects.
2. The carpet will not wear more than 25% in the 5 years following original purchase, provided the following:

The carpet is correctly bonded to the sub floor with the recommended adhesive.

The carpet is subject to normal foot and office traffic. Chair mats must be used where castor chairs are in intensive use.

The carpet is not subject to abnormal contamination, damp, water or other solvents, except as part of an approved maintenance programme, and that adequate barrier matting or other protection is provided in areas where traffic might carry contamination from outside or other areas.

The carpet is properly maintained from the date of installation.

The carpet is properly maintained and cleaned to Tier Global (UK) Limited recommended cleaning and maintenance methods. www.tier-global.com
3. In line with normal industry practice, this guarantee specifically excludes wear or damage caused by:

Footwear with studs, spikes or stiletto heels, castors; stairs where stair nosing have not been used, mechanical damage of any sort, damage due to cigarettes or burning and areas where a severe turning action or excessive or heavy traffic may occur.
4. This applies to loss of pile only and does not apply to crushing or soiling.
5. Any defect or discrepancy which could reasonably be found before or during laying must be reported immediately to Tier Global (UK) Limited.
6. Should the carpet fail to perform as specified in 1 or 2, the failed areas will be replaced with carpet of equal quality from the Tier Carpetlay range. The replacement carpet will be supplied free of charge with the addition of reasonable relaying costs. However Tier Global (UK) Limited cannot accept any liability for any consequential loss or claims arising from the replacement of the product.