

## Technical data sheet

Issue number 18.1 to check if you have our latest sheet visit [tier-global.com/download](http://tier-global.com/download)

### Product description

#### Product features

Tier Maintenance Oil is a hardening oil for maintaining and heavy cleaning of all oiled surfaces. Fast drying and low odour with good coverage.

#### Product uses

An oiled surface requires a maintenance treatment when it has got a grey or dirty look which no longer can be refreshed by regular cleaning. Tier Maintenance Oil can be used on all kinds of oiled floors; natural oils, 2 component oils and hard wax oils.

#### Packing

Packaged in metal can 1 litre .

### Technical information

#### Contents

Urethane modified pinewood oil, solvent paraffin. Solids 38%.

#### Usage

1 Litre for 40–80m<sup>2</sup>, depending on wood species and wood condition.  
Working temperature +15–30°C, drying time 3–8 hours after buffing.

### Usage guidelines

#### Application

Before using maintenance oil the surface has to be cleared of all loose particles which could otherwise damage the floor. The temperature of the room, the floor and the material must be between 15°C and 30°C. Underfloor heating must be switched off in good time before maintenance. Protect the floor from direct sunlight before, during and after application.

For application of Tier Maintenance Oil we recommend high quality red and white buffing pads.

#### Slightly soiled floors

Apply Marldon Satin Oil maintenance sparingly on the surface and work it into the wood with a cotton cloth or a buffer with a white pad. Continue buffing until the floor appears to be saturated and no more drops or smears are visible. Work systematically on an area of 10–15m<sup>2</sup> at a time, and ensure the overlaps are buffed carefully. Replace dirty cloths or pads as required. Allow a minimum of 3 hours drying time before use, preferably leave overnight. Do not use the floor during this period.

**NB** Oil saturated cloths and pads can self-ignite. Store used materials in water or in closed containers. The trowel and other tools can be cleaned with white spirit before the oil has hardened.

#### Heavily soiled floors

Apply Marldon Satin Oil maintenance generously and work it into the wood with a red pad. If the red pad does not give the desired effect, gradually increase the abrasion level of the pads. Clean off the dirty oil completely. When the floor appears to be clean and saturated, apply a new thin layer of Marldon Satin Oil maintenance, and buff with a white pad until no more drops or smears appear. Allow a minimum of 8 hours drying time before use, preferably leave overnight. Do not use the floor during this period.

### Storage

Store in dry conditions below 40°C.

#### Shelf life

2 years when stored as recommended in original unopened container. Once the can is opened the content might start hardening. Store upside down. Not sensitive to frost.

#### Health and safety

Product health and safety data sheets must be read and understood before use. Ensure good ventilation. Use protective goggles and gloves if there is any risk of splashing. If the product comes into contact with your skin, wash it off with soap and water. If the product gets into your eyes rinse with a generous amount of water. For further information see *Material safety data sheet*. Keep out of reach of children.

Tier Global (UK) Limited reserves the right to modify the content of technical data sheets without prior notice.