

Flexible metal magnet receptive sheeting technical data sheet

January 2019 to check if you have our latest sheet visit tier-global.com/download

Physical properties

Flexibility:	Can be coiled to ½" radius without cracking at 68°F
Hardness:	Shore D45
Machineability:	Die cutting, knife cutting, power saws, cleanly and with ease
Specific gravity:	3.6

Storage

Material should be stored in a dry place at a temperature range of 15°C to 25°C and 50% relative humidity with rolls stored horizontally in original packaging

Aftercare (dry erase finish)

For writing, we recommend the use of good quality dry marker pens. To avoid residual marks, we also advise regular cleaning with a good quality white board cleaner.

Do not use ballpoint pens or other sharp pointed writing instruments on the dry wipe surface.

Use non-abrasive cleaners. A household cleaner (eg Windolene) is acceptable. Rinse surfaces thoroughly with water after every cleaning.

Permanent markings may be removed with alcohol or by writing over the markings with a dry marker pen, then wiping clean.

Double-sided tissue tape

Description: A double-sided tissue tape with a high tack solvent acrylic adhesive. Hand tearable, good conformity, with a stable liner and excellent ultraviolet and plasticiser resistance. Ideal for bonding metal, nameplates, cloth and plastic surfaces.

Thickness: 0.09 mm

Adhesive: Solvent acrylic

Tensile strength: 0.71 Kg/cm

Elongation at break: 2%

Adhesion: 0.40 Kg/cm

Servicable temperature: -15°C to +120°C

Shelf Life: 12 Months

The above information is given in good faith and for guidance only. The user shall be responsible for determining that the performance of the product is sufficient for his application. The quoted values are based on averages and should not be taken as maximum or minimum values for specific purposes.

Guarantee:

Tier Global (UK) Ltd guarantees to investigate any complaints reported within 25 years from the date of sales invoice. In the event of a valid claim, Tier Global Ltd will provide replacement materials free of charge.

The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. For pre-finished floors our guarantee also covers the surface finish will adhere correctly to the boards and will not wear through for general residential use, when a preventative cleaning and maintenance program is in use.

Wood is a natural product and will expand and contract throughout the four seasons, during these seasons you may experience some natural movement which is not a product defect and is not covered by this guarantee.

As a general guideline, the ambient room temperature should be maintained between 15°C and 25°C and humidity levels between 45% and 65%. To maintain these humidity levels we would recommend using a humidifier/dehumidifier. Our guarantee is subject to your room conditions being maintained in accordance with British Standards 8201 current recommendations.

All complaints are to be reported in writing by post or email to info@tierglobal.com within 48 hours of the issue becoming visible, to allow us to investigate the cause and extent of the problem. Our guarantee is subject to our terms and conditions.

Tier Global (UK) Limited reserves the right to modify the content of technical data sheets without prior notice.