


Magnetic engineered wooden flooring technical data sheet

May 2024 to check if you have our latest sheet visit tier-global.com/

TIERdrylay™
FLOORING SYSTEMS

Thickness	140mm wide	180mm wide	220mm wide
13mm (including magnetic backing)	NA	TIER 379 001-012	TIER 379 013-024
16mm (including magnetic backing)	TIER 379 100-111	TIER 379 200-211	TIER 379 300-311



Description	Dry Lay magnetic backed and sealed engineered planks for superior coverings on raised access flooring
Wood species:	European Oak, prime/rustic
Approval:	FSC 100%, anti-slip
Lengths:	Random 600–2400mm (average 1800–2200mm)
Profile:	Tongue and groove ends, Q-Lon polyurethane foam seal and 1.5mm bevel to long sides. Magnetic base.
Finished:	Filled and sanded / bespoke finish
Construction:	13mm – 3mm Oak wear layer, 9mm multi-layer Birch plywood and 1mm magnetic backing
Construction:	16mm– 4mm Oak wear layer, 11mm multi-layer Birch plywood and 1mm magnetic backing
Lamination:	Hydraulic cold press
Glue line:	D3 water based glue
Norm:	DIN EN 13489: 2002 Multilayer Flooring
Reaction to fire:	Dfls1
Density:	685 Kg/m ³
Formaldehyde emissions:	Class E1 zero emissions
Warmth conduction:	15mm-0.091 W/m ² K
Site conditions:	45–65% relative humidity and 18–20°C room temperature
D/S adhesive P2:	A clear PET Film with high performance adhesive, providing excellent long term bonding and strong holding power. Suitable for high temperature use. Tear resistant liner for excellent die-cutting attributes

Good resistance to UV, chemicals, weather conditions, aging and plasticisers

Thickness: 0.2mm–0.21mm
Temperature resistance:
short term 200°C, long term 100°C

Magnetic backing: Strontium ferrite isotropic magnetic sheet
0.75mm thick – Attractive Force = 38g/cm²

Magnetic properties: Energy (BH Max): 0.6 MGOe

Residual induction Br (Gauss): 1600-1800 Gs

Intrinsic coercive force Hcl (Oersteds): 2405 Oe

Coercive force HcB (Oe): 1306 Oe

Physical properties: Can be coiled to 13mm radius @ 68°F without cracking

Hardness: Shore D45

Machinability: die cutting, knife cutting, power saws, cleanly and with ease

Specific gravity: 3.6

Q-Lon seal: Polyurethane foam seal, acoustic seal, anti squeak, water resistant, cold smoke proof. Tested up to 20 years

Temp range: -60°C to +70°C

Abrasion resistance: No abrasion after 285,000 cycles of grinding load

Installation method: All new access floors should be installed to SR1 standard. Pedestals must be adjusted and levelled to eliminate any rocking or lipping of the raised access panel. The locking nut on the pedestal should be utilised to avoid any opportunity of the pedestal moving during its lifespan. Where possible, the access panels should be fixed to the pedestal. If this is not possible as with some brands, SR1 standard must be achieved. See our 'Tier tips' in our full Installation and maintenance guidelines to ensure a perfect installation.

Ensure Steel surface on raised access floor is clean from debris and dust to get maximum magnetic bond before laying random planks. Boards can be cut with ease with a cross cutting saw blade, Manual or power.

Removal method: To remove the boards for access, use a suction cup tool. Apply a small amount of washing up liquid to the cup, apply suction cups tool to the surface of the plank to be lifted, next to a joint. Apply pressure whilst you

engage the suction cups mechanism ensuring a full seal, and lift. Surrounding boards need only small lever to break the magnetic bond at an edge, and planks will lift with ease.

Underfloor heating: This product is compatible with underfloor heating. Temperature resistances listed above.

Cleaning method: Ensure you use the correct Tier Global cleaning materials. Please check our website for the correct cleaning solution to use on TIER drylay floors. Do not clean wood flooring with water alone as this will create a high risk of surface coating failure. Clean away any residues on the floor quickly.

Guarantee: Tier Global guarantees to investigate any complaints reported within two years from the date of sales invoice. In the event of a valid claim, Tier Global will provide replacement materials free of charge.

The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. For pre-finished floors our guarantee also covers the surface finish will adhere correctly to the boards and will not wear through for general residential use, when a preventative cleaning and maintenance programme is in use. Wood is a natural product and will expand and contract throughout the four seasons, during these seasons you may experience some natural movement which is not a product defect and is not covered by this guarantee.

As a general guideline, the ambient room temperature should be maintained between 15 and 25°C and humidity levels between 45 and 65%. To maintain these humidity levels we would recommend using a humidifier/dehumidifier. Our guarantee is subject to your room conditions being maintained in accordance with British Standards 8201 current recommendations.

Tier Global maintenance products should be used to maintain the warranty (samples available).

All complaints are to be reported in writing by post or email to info@tierglobal.com within 48 hours of the issue becoming visible, to allow us to investigate the cause and extent of the problem. Our guarantee is subject to our terms and conditions.

Tier Global reserves the right to modify the content of technical data sheets without prior notice.